P2000K Subcompact 9mm & .40 S&W Semi-automatic Pistol



HECKLER & KOCH INC.

21480 Pacific Boulevard Sterling, Virginia 20166 U.S.A. Tel (703) 450-1900 • Fax (703) 450-8160 www.hk-usa.com



Like the slightly larger P2000 US model, the P2000K Subcompact combines elements of the successful HK USP Compact pistol with recent technological innovations from HK engineers—only in a smaller, more concealable design.

The P2000K Subcompact uses the trigger system introduced in 2001 on the USP Compact "LEM" (Law Enforcement Modification) model.

This unique pre-cocked hammer system combines the advantages of a cocked striker component (constant level of trigger pull and short trigger travel from first to last round fired) with a double action hammer system. The LEM trigger pull has been reduced to 7.3-8.5 pounds of pressure (32.5 Newtons), compared to 12-15 pounds found on many conventional double action pistols. Optional adjustment (by HK armorers) can bring the trigger pull into the 5.5 pound range.

Using such an enhanced trigger system consolidates ease of use and safety into a convenient, innovative trigger operation—one that prevents unintended firing. And in case of

HK P2000 US Subcompact (right view) an ammunition-related failure to fire, all that is needed is an additional second or third pull of the trigger without the need of first pulling the slide back to re-cock the subcompact.

The enhanced LEM trigger system combines the reliability of a double-action revolver trigger with the crisp, precise trigger of a single-action pistol. For shooters that prefer a conventional double-action/single-action pistol, a special DA/SA variant is planned with a decock button mounted on the rear of the frame.

A choice of two simple-to-install grip panels make it easy to custom-fit the P2000 Sub-compact to any shooter's hand. And the same ambidextrous magazine release and dual slide release levers found on the P2000 make handling the Subcompact easy for both right and left-handed shooters.

A set of abbreviated "industry standard" mounting rails on the P2000K Subcompact, enable lights, aimers, and other accessories to be added by sliding them onto the open rail system. The HK P2000K Subcompact also can use widely available, reliable USP Compact magazines.

Features

industry-standard mounting rails for installing accessories
 ambidextrous slide release (located on both sides of the frame)
 ideal size for concealed carry
 optional magazine disconnect
 ambidextrous magazine release lever
 corrosion proof fiber-reinforced polymer frame
 polygonal bore profile for increased velocity, easier cleaning, and longer barrel life
 low profile slide and slimline, compact

dimensions • very short trigger reset distance to enhance the speed of multiple or follow-up shots • replaceable grip panels for custom fit • polymer recoil absorber bushing aids in recoil reduction • corrosion resistant "Hostile Environment" blued finish • oversized tapered trigger guard for use with gloves • patented Lock-Out Safety device • limited lifetime warranty for civilian sales / one year for law enforcement and military

P2000K SUBCOMPACT TECHNICAL SPECIFICATIONS

Caliber 9mm x 19 and 40 S&W Operation Short recoil, modified Browning type, linkless Mode of Fire Semi-automatic **Magazine Capacity** 10-round (9mm) 9-round (.40 S&W) Fixed patridge style drift Sights adjustable for windage, standard 3-dot Length (Overall) 6.42 inches (163 mm)

Barrel Length
Barrel Profile
Width (Overall)
Height
Weight (with empty magazine)

2.48 inches (83 mm)
Polygonal
1.28 inches (32 mm)
4.61 inches (117 mm)

 Weight (with empty magazine)

 9mm
 1.49 pounds (675 grams)

 .40 S&W
 1.61 pounds (730 grams)