

HECKLER & KOCH INC.

21480 Pacific Boulevard Sterling, Virginia 20166 U.S.A. Tel (703) 450-1900 • Fax (703) 450-0721 www.hk-usa.com



Like the slightly larger P2000 US model, the P2000 SK Subcompact combines elements of the successful HK USP Compact pistol with recent technological innovations from HK engineers—only in a smaller, more concealable design.

The P2000 SK Subcompact uses the trigger system introduced in 2001 on the USP Compact "LEM" (Law Enforcement Modification) model.

This unique pre-cocked hammer system combines the advantages of a cocked striker component (constant level of trigger pull and short trigger travel from first to last round fired) with a double action hammer system. The LEM trigger pull has been reduced to 7.3-8.5 pounds of pressure (32.5 Newtons), compared to 12-15 pounds found on many conventional double action pistols. Optional adjustment (by HK armorers) can bring the trigger pull into the 5.5 pound range.

Using such an enhanced trigger system consolidates ease of use and safety into a convenient, innovative trigger operation—one that prevents unintended firing. And in case of an ammunition-related failure to fire, all that is

H K P2000 SK Subcompact (right view) needed is an additional second or third pull of the trigger without the need of first pulling the slide back to re-cock the subcompact.

The enhanced LEM trigger system combines the reliability of a double-action revolver trigger with the crisp, precise trigger of a single-action pistol. For shooters that prefer a conventional double-action/single-action pistol, a special DA/SA variant is planned with a decock button mounted on the rear of the frame.

A choice of two simple-to-install grip panels make it easy to custom-fit the P2000 SK Subcompact to any shooter's hand. And the same ambidextrous magazine release and dual slide release levers found on the P2000 make handling the Subcompact easy for both right and left-handed shooters.

A set of abbreviated "industry standard" mounting rails on the P2000 SK Subcompact, enable lights, aimers, and other accessories to be added by sliding them onto the open rail system. The HK P2000K Subcompact also can use widely available, reliable USP Compact magazines.

Features

• industry-standard mounting rails for installing accessories • ambidextrous slide release (located on both sides of the frame) • ideal size for concealed carry • optional magazine disconnect • ambidextrous magazine release lever • corrosion proof fiber-reinforced polymer frame • polygonal bore profile for increased velocity, easier cleaning, and longer barrel life • low profile slide and slimline, compact dimensions • very short trigger reset distance to

enhance the speed of multiple or follow-up shots
• replaceable grip panels for custom fit •
polymer recoil absorber bushing aids in recoil
reduction • corrosion resistant "Hostile
Environment" blued finish • oversized tapered
trigger guard for use with gloves • patented LockOut Safety device • limited lifetime warranty for
civilian sales / one year for law enforcement and
military

P2000 SK SUBCOMPACT TECHNICAL SPECIFICATIONS

Caliber Operation

Sights

9mm x 19 and .40 S&W Short recoil, modified Browning type, linkless Semi-automatic

Mode of Fire Semi-automatic
Magazine Capacity 10-round (9mm)
9-round (40 S&)

9-round (.40 S&W) Fixed patridge style drift adjustable for windage,

standard 3-dot 6.42 inches (163 mm)

Length (Overall)

Barrel Length
Barrel Profile

Width (Overall)

6.42 inches (163 mm)
2.48 inches (83 mm)
Polygonal
1.28 inches (32 mm)

Width (Overall) 1.28 inches (32 mm)
Height 4.61 inches (117 mm)
Weight (with empty magazine)

9mm | 1.49 pounds (675 grams) .40 S&W | 1.61 pounds (730 grams) Empty Magazine | 2.65 ounces (75 grams) Trigger Pull (LEM) | 7.42 pounds (33 N) (DA/SA) | 10.34/4.04 pounds (46/18 N)